



SuperQuilt

TECHNICAL DATA SHEET

YBS SuperQuilt is a UK leading performer of reflective multi-foil insulation. UK manufactured and certified to the highest standards including LABC and BDA Agrément approval, Superquilt provides outstanding thermal and vapour control properties.

SuperQuilt


SuperQuilt-Insulation.co.uk

- ✓ **High thermal resistance of 3.0m²K.W**
- ✓ **UK manufactured**
- ✓ **2 in 1 insulation and vapour control membrane**
- ✓ **NHBC acceptance**
- ✓ **LABC certified**
- ✓ **Thermally tested in accordance with EN16012**
- ✓ **Quick and easy to install**
- ✓ **Reduces waste**
- ✓ **Flexible and easy to install**
- ✓ **Building Control compliant**
- ✓ **Non degradable maintaining thermal performance and integrity**
- ✓ **Unique, patented kimble design holds layers in place to avoid separation when cutting**

PRODUCT DETAILS		
Layers	19	
Thickness (mm)	40	
Weight (g/m ²)	800	
MECHANICAL PROPERTIES		
Thermal Performance	Value	Standard
Core	1.52m ² K/W	BS EN 16012
Roof	2.50m ² K/W	BS EN 6946
Wall	3.00m ² K/W	BS EN 6946
Floor	4.45m ² K/W	BS EN 6946
Flammability	Class E	BS EN 13501-1
Water Vapour Resistance	1596MNs/g	BS EN 12572
Emission Coefficients of surfaces	0.02	BS EN 16012
Tensile Strength	142KPA	BS EN 1608
PACKAGING		
Area	15m²	12m²
Width (m)	1.5	1.2
Length (m)	10	10
Weight (Kg)	12.5	9.9



Scan QR Code!
Buy SuperQuilt Online
At the Lowest Trade
Prices Here!



SuperQuilt is a multi-purpose nineteen layer Insulation blanket suitable for roof, walls and floor applications. This versatile thermally efficient layered insulation is the ideal solution to all your insulation needs and will save valuable **time** and **cost** of your installation whilst providing energy savings and maximising living space.

ROOF APPLICATIONS


- 04.** General Fixing Instructions
- 05.** Under Rafter Pitched Roof
- 06.** Under Rafter/Over Rafter Pitched Roof
- 07.** Two Layer Pitched Roof
- 08.** Under Rafter Flat Roof
- 10.** Over Rafter Flat Roof
- 11.** Two Layer Flat Roof
- 12.** Recessed Details
- 13.** Purlins Details
- 13-14.** Detailing

WALL APPLICATIONS

- 16.** General Fixing Instructions
- 17.** Timber Frame and Dormer Cheeks
- 18.** Cavity Wall
- 19.** Dry Lining
- 20.** Dwarf Wall
- 21.** External Render

FLOOR APPLICATIONS

- 22.** General Fixing Instructions
- 23.** Suspended Timber Floor
- 24.** Floating Timber Floor
- 25.** Crawl Space Floor



ROOF INSULATION

INSULATION FOR USE IN ROOFS

YBS SuperQuilt is flexible, easy to install, multi-foil insulation suitable for roofs, walls and floors. Made up of nineteen layers and only 40mm in thickness, the unique composition effectively deals with all forms of energy transfer. The unique patented technology allows the material to expand where necessary, increasing overall thermal performance.

HOW DOES SUPERQUILT WORK?

Due to the special composition of multi-layers of insulation, SuperQuilt effectively deals with all forms of energy transfer (i.e. conduction, convection and radiation). SuperQuilt works most effectively by reflecting infra-red radiation. This means that not only is SuperQuilt effective in winter by reflecting heat back into the building and cold out, but also in summer SuperQuilt is a very effective barrier to solar overheating which reduces the need for artificial cooling systems as it prevents the accumulation of heat within the building.

GENERAL FIXING INSTRUCTIONS

Installation of SuperQuilt for pitched roof applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt must be installed with a 50mm overlap with all joints taped with **ThermaSeal Foil Tape**.

SuperQuilt can be cut with a YBS SuperQuilt cutter, craft knife or a sharp pair of scissors.

SuperQuilt can be easily fixed with staples at regular intervals. Minimum 14mm stainless steel or galvanised staples are recommended.

SuperQuilt is most effective with a minimum 25mm air gap on either side. Battens can be used to create this gap. No protective clothing/handling required.

BENEFITS

- **NHBC Acceptance**
- **Meets requirements of L1A and L1B 2010 addition**
- **In accordance with BR443**
- **Fully Agrément certified**
- **Thermally tested in accordance with EN16012**
- **High thermal resistance of 2.50m²K/W**
- **Effective solar over-heating barrier**
- **Effective in summer and winter**
- **Lightweight, thin & flexible**
- **Fast and simple installation**
- **Tear resistant**
- **For flat roofs and pitched roofs between 20° and 70°**

Fixing Instructions

Installation of SuperQuilt for under rafter applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt is applied directly from the roll either vertically or horizontally depending on the rafter height, pulled tight and stapled onto the rafters at minimum 300mm centres.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the rafters, the joints should be sealed using **ThermaSeal Foil Tape**.

Additionally, at the eaves SuperQuilt is cut around the rafters and sealed to the Cavity wall insulation or wall plate.

Fix 25mm by 38mm battens at right angel to rafters. Battens must always be fixed around the perimeter of windows.

The plasterboard is fixed over the SuperQuilt and onto the battens in the usual manner. When installed below rafters SuperQuilt will perform as a vapour barrier.




View SuperQuilt Under Rafter Installation video
Scan QR Code Here!

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.040
Slate/Tile	10.00	-	-
Batten Cavity	25.00	-	-
Breather Membrane	-	-	-
Rafter Cavity	30.00	-	0.340
Rafters / PIR Insulation	70.00	0.022	3.182
Rafter Cavity	25.00	-	0.490
SuperQuilt	7.00	-	1.520
Batten Cavity	25.00	-	0.490
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.100
Total Resistance			6.292

Example Construction



U-Value table

Description (rafters at 400mm centres)

SuperQuilt and 75mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 130mm Glasswool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 110mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 140mm PIR (0.022 W/mk)	0.13 W/m ² k

Description (rafters at 600mm centres)

SuperQuilt and 70mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm Glasswool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 95mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 125mm PIR (0.022 W/mk)	0.13 W/m ² k

Fixing Instructions

SuperQuilt should be installed under rafter as per the instructions shown on page 05. BreatherQuilt should then be installed over rafter.

Installation of BreatherQuilt for pitched roof applications and additional insulation products should be in accordance with the manufacturer's certificate, fixing instructions and current good building practice.

Start at the bottom of the roof by rolling BreatherQuilt across the rafters and staple in to place, additional rolls should be butt jointed and sealed using waterproof tape. Tape a line of double sided tape along the top edge of the material.

Install the next layer of BreatherQuilt overlapping the material by 75mm, staple as before and then secure with the double sided tape, additional rolls should be butt jointed and sealed using waterproof tape

BreatherQuilt can be cut with craft knife or a sharp pair of scissors. Staple at regular intervals using minimum 14mm stainless steel or galvanized staples are recommended. No protective clothing/handling required.

Watch our How-To Video For BreatherQuilt over rafter by scanning the QR Code Here!



U-Value table

Description (rafters at 400mm centres)

SuperQuilt/40mm PIR (0.022 W/mk)/BreatherQuilt (Draped)	0.18 W/m ² k
SuperQuilt/60mm Mineral Wool (0.035W/mk)/BreatherQuilt (Draped)	0.18 W/m ² k
SuperQuilt/100mm PIR (0.022 W/mk)/BreatherQuilt (Draped)	0.13 W/m ² k
SuperQuilt/150mm Mineral Wool (0.035W/mk)/BreatherQuilt (Draped)	0.13 W/m ² k


Description (rafters at 600mm centres)

SuperQuilt/40mm PIR (0.022 W/mk)/BreatherQuilt (Draped)	0.18 W/m ² k
SuperQuilt/60mm Mineral Wool (0.035W/mk)/BreatherQuilt (Draped)	0.18 W/m ² k
SuperQuilt/100mm PIR (0.022 W/mk)/BreatherQuilt (Draped)	0.13 W/m ² k
SuperQuilt/150mm Mineral Wool (0.035W/mk)/BreatherQuilt (Draped)	0.13 W/m ² k

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.100
Slate/Tile	10.00	-	-
Tile Batten	19.00	-	-
Rafters / BreatherQuilt(Draped)	40.00	-	1.017
Rafters Cavity	20.00	-	0.450
Rafters / PIR Insulation	40.00	0.022	1.818
Rafter Cavity	25.00	-	0.490
SuperQuilt	7.00	-	1.52
Batten Cavity	25.00	-	0.490
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.100
Total Resistance			5.804

Example Construction



Fixing Instructions

Installation of SuperQuilt for under rafter applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

For recessed installation please see page 12.

For under rafter installation please see page 5 fixing instructions.

When installing two layers of SuperQuilt a 38mm air space should be maintained between layers at all times.


Watch our How-To Video For SuperQuilt Under Rafter by scanning the QR Code Here!



Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.040
Slate/Tile	10.00	-	-
Batten Cavity	25.00	-	-
Roofing Membrane	-	-	-
Rafter Cavity	38.00	-	0.490
SuperQuilt (Recessed)	40.00	-	1.520
Rafter Cavity	38.00	-	0.490
SuperQuilt	7.00	-	1.520
Batten Cavity	25.00	-	0.490
Insulated Plasterboard	32.50	-	1.070
Inside Surface	-	-	0.100
Total Resistance			5.72

Example Construction



U-Value table

Description (rafters at 400mm centres)

SuperQuilt (2 Layers) with 40mm insulated Plasterboard (XPS) (1.070 m ² K/W)	0.18 W/m ² k
SuperQuilt (2 Layers) with 37.5mm insulated Plasterboard (PIR) (2.2 m ² K/W)	0.18 W/m ² k
SuperQuilt (2 Layers) and 57.5mm Insulated Plasterboard (PIR) (2.2 m ² K/W)	0.15 W/m ² k
SuperQuilt (2 Layers) and 80mm PIR (0.022 W/mK)	0.13 W/m ² k

Description (rafters at 600mm centres)

SuperQuilt (2 Layers) with 40mm insulated Plasterboard (XPS) (1.070 m ² K/W)	0.18 W/m ² k
SuperQuilt (2 Layers) and 45mm PIR (0.022 W/mK)	0.15 W/m ² k
SuperQuilt (2 Layers) and 57.5mm Insulated Plasterboard (PIR) (2.2 m ² K/W)	0.15 W/m ² k
SuperQuilt (2 Layers) and 70mm PIR (0.022 W/mK)	0.13 W/m ² k

Fixing Instructions

Installation of SuperQuilt for under joist flat roof applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the joists, the joints should be sealed using ThermaSeal Foil Tape when SuperQuilt is cut to fit around openings or connections, gaps must be minimized and any exposed cut edges should be sealed with ThermaSeal Foil Tape to prevent condensation.

SuperQuilt should be cut equal to the width of the roof section plus 100mm. Installation should start from the external wall with SuperQuilt being unrolled perpendicular to the joists, after which it is fixed using staples, nails or YBS saddle clips.

SuperQuilt should be held in place using timber battens or by other means as shown, in such a way that there is a nominal 25mm air cavity above the product (if applicable) and a nominal 25mm air cavity below. To minimize the effect of thermal bridging cross battening is advised.

When installed below joists SuperQuilt will perform as a vapour barrier.

U-Value table

Description (rafters at 400mm centres)

SuperQuilt and 160mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 140mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 180mm Mineral Wool (0.033 W/mk)	0.15 W/m ² k
SuperQuilt and 100mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 135mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 165mm PIR (0.022 W/mk)	0.13 W/m ² k


Description (rafters at 600mm centres)

SuperQuilt and 150mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 125mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 170mm Mineral Wool (0.033 W/mk)	0.15 W/m ² k
SuperQuilt and 90mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 145mm PIR (0.022 W/mk)	0.13 W/m ² k

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mk)	Resistance (m ² K/W)
EPDM	-	-	-
Ply decking	-	-	-
Joist Cavity (ventilated)	50.00	-	0.170
Joist / PIR Insulation	100.00	0.022	4.545
SuperQuilt	7.00	-	1.520
Batten Cavity	25.00	-	0.490
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.100
Total Resistance			6.891

Example Construction



Fixing Instructions

Installation of SuperQuilt for under joist flat roof applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the joists, the joints should be sealed using ThemaSeal Foil Tape when SuperQuilt is cut to fit around openings or connections, gaps must be minimized and any exposed cut edges should be sealed with ThemaSeal Foil Tape to prevent condensation. SuperQuilt should be cut equal to the width of the roof section plus 100mm. Installation should start from the external wall with SuperQuilt being unrolled perpendicular to the rafters, after which it is fixed using staples, nails of YBS Saddle Clips.


SuperQuilt should be held in place using timber battens or by other means as shown, in such a way that there is a nominal 25mm air cavity above the product (if applicable) and a nominal 25mm air cavity below. To minimize the effect of thermal bridging cross battening is advised.

When installed below joists SuperQuilt will perform as a vapour barrier.

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mk)	Resistance (m ² K/W)
EPDM	-	-	-
Ply decking	-	-	-
Cavity (ventilated)	50.00	-	0.170
Joist / PIR Insulation	90.00	0.022	4.091
Cavity (non-ventilated)	25.00	-	0.490
SuperQuilt	7.00	-	1.520
Batten Cavity	25.00	-	0.490
Plasterboard	12.50	-	0.066
Inside Surface	-	-	0.100
Total Resistance			6.927

Example Construction



U-Value table

Description (rafters at 400mm centres)

SuperQuilt and 140mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 170mm Mineral Wool (0.033 W/mk)	0.15 W/m ² k
SuperQuilt and 90mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 150mm PIR (0.022 W/mk)	0.13 W/m ² k

Description (rafters at 600mm centres)

SuperQuilt and 130mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 110mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 150mm Mineral Wool (0.033 W/mk)	0.15 W/m ² k
SuperQuilt and 80mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 110mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 135mm PIR (0.022 W/mk)	0.13 W/m ² k

Fixing Instructions

Installation of SuperQuilt for over joist flat roof applications and additional insulation products should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the joists, the joints should be sealed using YBS Foil Tape. When SuperQuilt is cut to fit around openings or connections, gaps must be minimized and any exposed cut edges should be sealed with YBS Foil Tape to prevent condensation.


SuperQuilt should be cut equal to the width of the roof section plus 100mm. Installation should start from the external wall with SuperQuilt being unrolled perpendicular to the rafters, after which it is fixed using staples or nails or with saddle clips. SuperQuilt should be held in place using timber battens or by other means as shown, in such a way that there is a nominal 25mm air cavity above the product (if applicable) and a nominal 25mm air cavity below. To minimize the effect of thermal bridging cross battening is advised.

Additional insulation should be installed above the SuperQuilt. When installed below rafters SuperQuilt will perform as a vapour barrier.

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
EPDM	-	-	0.040
PIR	65.00	0.022	2.955
Ply decking	18.00	0.130	0.138
Joist / Non-Ventilated Cavity	25.00	-	0.490
SuperQuilt (Recessed)	14.00	-	1.520
Joist / Non-Ventilated Cavity	75.00	-	0.490
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.100
Total Resistance			5.799

Example Construction



U-Value table (All calculations are based on 50mm joists and include the effect of cold bridging)

Description (rafters at 400mm centres)

SuperQuilt and 65mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 90mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 105mm PIR (0.022 W/mk)	0.13 W/m ² k
SuperQuilt and 85mm XPS (0.029 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm XPS (0.029 W/mk)	0.15 W/m ² k
SuperQuilt and 140mm XPS (0.029 W/mk)	0.13 W/m ² k

Description (rafters at 600mm centres)

SuperQuilt and 65mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 90mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 105mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 85mm XPS (0.029 W/mk)	0.18 W/m ² k
SuperQuilt and 120mm XPS (0.029 W/mk)	0.15 W/m ² k
SuperQuilt and 135mm XPS (0.029 W/mk)	0.13 W/m ² k

Fixing Instructions

Installation of SuperQuilt for over and under rafter flat roof applications with additional insulation should be in accordance with the manufacturers certificate, fixing instructions and current good building practice.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the rafters, the joints should be sealed using YBS Foil Tape. When SuperQuilt is cut to fit around openings or connections, gaps must be minimized and any exposed cut edges should be sealed with ThermaSeal Foil Tape to prevent condensation.

SuperQuilt should be cut equal to the width of the roof section plus 100mm. Installation should start from the external wall with SuperQuilt being unrolled perpendicular to the joists, after which it is fixed using staples, nails or YBS saddle clips.

SuperQuilt should be held in place using timber battens or by other means as shown, in such a way that there is a nominal 25mm air cavity above the product (if applicable) and a nominal 25mm air cavity below. To minimize the effect of thermal bridging cross battening is advised.

When installed below joists SuperQuilt will perform as a vapour barrier.

U-Value table

Description (rafters at 400mm centres)

SuperQuilt and 50mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 100mm Mineral Wool (0.040 W/mk)	0.15 W/m ² k
SuperQuilt and 40mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 30mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 65mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 75mm PIR (0.022 W/mk)	0.13 W/m ² k


Description (rafters at 600mm centres)

SuperQuilt and 50mm Mineral Wool (0.040 W/mk)	0.18 W/m ² k
SuperQuilt and 90mm Mineral Wool (0.040 W/mk)	0.15 W/m ² k
SuperQuilt and 40mm Mineral Wool (0.033 W/mk)	0.18 W/m ² k
SuperQuilt and 25mm PIR (0.022 W/mk)	0.18 W/m ² k
SuperQuilt and 55mm PIR (0.022 W/mk)	0.15 W/m ² k
SuperQuilt and 65mm PIR (0.022 W/mk)	0.13 W/m ² k

Example U-Value

U-Value Combined Method (W/m ² K)			0.18
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
EPDM	-	-	0.040
Ply decking	18.00	0.130	0.138
Non-Ventilated Cavity	25.00	-	0.490
SuperQuilt (Recessed)	40.00	-	1.520
Joist / Non-Ventilated Cavity	25.00	-	0.490
PIR	25.00	0.022	1.136
SuperQuilt	14.00	-	1.520
Batten Cavity	25.00	-	0.490
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.100
Total Resistance			5.990

Example Construction



Under Rafter Application

Ensure that there is an airspace above the SuperQuilt at all times.


1. SuperQuilt is stapled to the underside of the first rafter.
2. SuperQuilt is recessed into the rafter void and fixed with staples or with battens.
3. The material is then fixed to opposite rafter as per instruction 2.
4. SuperQuilt is then wrapped around the rafter and the procedure starts again.

Once all the SuperQuilt is fitted, all joints should be taped using YBS Foil tape. Plasterboard can then be fixed directly to the underside of the rafters below the SuperQuilt.

Watch our How-To Video For SuperQuilt Under Rafter by scanning the QR Code Here!



Under Rafter Application




Between Purlins Application

SuperQuilt is fixed horizontally or vertically and stapled to the underside of the the rafters.

At the purlins the SuperQuilt is turned up and stapled in place.

Perpendicular Battens are fixed through the SuperQuilt into the rafters, at the purlins the battens are fixed into the rafters crushing the SuperQuilt tightly against the purlins.

Plasterboard can then be fixed to the battens.




Around Purlins Application

SuperQuilt is fixed horizontally or vertically and stapled to the underside of the the rafters.

At the purlins the SuperQuilt is cut and pushed behind the purlins then taped to the next piece at the opposite side of the purlin.

Perpendicular Battens are fixed through the SuperQuilt into the rafters.

Plasterboard can then be fixed to the battens.



Detailing

Fixing Instructions

SuperQuilt is fixed above rafters as per fixing details and turned up at the vent/wall/rooflight and sealed with YBS Foil Tape. Battens are placed on the rafters above the SuperQuilt. A breather membrane is fixed above the battens and finished by turning up at the vent/wall/rooflight and sealing to the vent/wall/rooflight. Tile battens are fixed in place. The flashing/collar for the vent/wall/rooflight is fitted above the tile battens and then tiles.

Foil taped joints

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the battens, the joints should be sealed using ThermaSeal Foil Tape.

Vapour control layer

When all joints are sealed using foil tape SuperQuilt also works as a vapour control layer.

- Multifoil Fitting Kit Recommended
- ThermaSeal Foil Tape 75mm x 50m Recommended


Under Rafter Fixing Details

SuperQuilt is stapled to the underside of the rafters. At the eaves the SuperQuilt is cut and taken down between the joists to the cavity wall insulation or the wall plate. The material needs to be fixed to the rafters with minimum 14mm staples and taped to the joists and cavity wall insulation or wall plate so that an airtight envelope is created.


Over Rafter Fixing Details

SuperQuilt is stapled to the rafters. At the eaves the SuperQuilt is cut and taken down between the rafters to the cavity wall insulation or the wall plate. The SuperQuilt needs to be sealed with staples and taped to the rafters and the cavity wall insulation or wall plate to create an airtight envelope.


Vents / Light Pipes




Flashing




Rooflight




Eaves



Valleys



Downlighters





WALL INSULATION

INSULATION FOR USE IN WALLS

HOW DOES SUPERQUILT WORK?

Due to the special composition of multi-layers of insulation, SuperQuilt effectively deals with all forms of energy transfer (i.e. conduction, convection and radiation). SuperQuilt works most effectively by reflecting infra-red radiation. This means that not only is SuperQuilt effective in winter by reflecting heat back into the building and cold out, but also in summer SuperQuilt is a very effective barrier to solar overheating which reduces the need for artificial cooling systems as it prevents the accumulation of heat within the building.

GENERAL FIXING INSTRUCTIONS

Installation of SuperQuilt for Timber Frame and Masonry Wall Applications and additional insulation products should be in accordance with the Certificate, YBS fixing instructions and current good building practice.

When the SuperQuilt is cut to fit around openings, care should be taken to minimise gaps. SuperQuilt can be cut easily using sharp scissors or a knife.

The surfaces of the masonry wall should be sound and free from loose material; large projections should be removed and holes filled and levelled. A survey of the wall may be required to establish the extent of any packing that may be required to ensure a uniform plane for the materials to be fixed.

Bearing surfaces for timber battens should comply with BS 8212 : 1995. The depth of timber battens will determine the air space achieved on either side of the SuperQuilt, YBS recommend 25mm battens.

All joints and perforations in the products must be securely sealed with ThermaSeal Foil Tape.

Services may be accommodated within the void created by the dry lining system.

If the wall you are refurbishing has a damp or mould issue, this needs to/must be rectified before any insulation is installed.

BENEFITS

- Meets requirements of L1A, L1B 2010
- Fully Agrément certified
- Thermally tested in accordance with EN 16012
- High thermal resistance of up to 3.00m²K/W
- Ideal for new build & refurbishment
- Effective solar over-heating barrier
- Lightweight, thin & flexible
- Fast and simple installation
- Vapour control layer

Fixing Instructions

Installation of SuperQuilt for Timber Frame wall applications and additional insulation products should be in accordance with the certificate, YBS fixing instructions and current good building practice.

SuperQuilt is applied directly from the roll either vertically or horizontally depending on the wall height, pulled tight and stapled onto the timber studs at minimum 300mm centres.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the battens, the joints should be sealed using ThermaSeal Foil Tape.


Perpendicular counter battens, recommended 25mm by 38mm are fixed to the wall. Battens must always be placed at the top and bottom of the wall and around the perimeter of doors and windows.

The plasterboard is fixed over the materials and onto the battens in the usual manner.



Watch our How-To Video For SuperQuilt & BreatherFoil FR on Timber Frame Walls by scanning the QR Code Here!

U-Value Combined Method (W/m ² K)			0.24
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.060
Brick, External	102.50	0.770	0.133
Cavity	50.00	-	0.665
BreatherFoil FR	4.00	-	0.125
Sheathing Board	12.00	0.130	0.092
Stud Cavity	89.00	-	0.740
SuperQuilt	7.00	-	1.52
Batten Cavity	38.00	-	0.740
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.120



U-Value table

Description

SuperQuilt and YBS BreatherFoil FR

25mm Batten

0.25 W/m²k

38mm Batten

0.24 W/m²k

SuperQuilt, YBS BreatherFoil FR and 50mm Glasswool (0.040 W/mk)

0.21 W/m²k

0.20 W/m²k

SuperQuilt, YBS BreatherFoil FR and 100mm Glasswool (0.040 W/mk)

0.17 W/m²k

0.16 W/m²k

SuperQuilt, YBS BreatherFoil FR and 25mm PIR (0.022 W/mk)

0.21 W/m²k

0.20 W/m²k

SuperQuilt, YBS BreatherFoil FR and 50mm PIR (0.022 W/mk)

0.18 W/m²k

0.17 W/m²k

SuperQuilt, YBS BreatherFoil FR and 100mm PIR (0.022 W/mk)

0.14 W/m²k

0.14 W/m²k

SuperQuilt, YBS BreatherFoil FR and 140mm PIR (0.022 W/mk)

0.13 W/m²k

0.12 W/m²k

SuperQuilt, YBS BreatherFoil and SuperQuilt

0.17 W/m²k

0.17 W/m²k

SuperQuilt, Standard Breather Membrane

0.30 W/m²k

0.28 W/m²k

SuperQuilt, Standard Breather Membrane and 50mm Glasswool (0.040 W/mk)

0.24 W/m²k

0.22 W/m²k

SuperQuilt, Standard Breather Membrane and 100mm Glasswool (0.040 W/mk)

0.19 W/m²k

0.18 W/m²k

SuperQuilt, Standard Breather Membrane and 25mm PIR (0.022 W/mk)

0.25 W/m²k

0.23 W/m²k

SuperQuilt, Standard Breather Membrane and 50mm PIR (0.022 W/mk)

0.21 W/m²k

0.20 W/m²k

SuperQuilt, Standard Breather Membrane and 100mm PIR (0.022 W/mk)

0.16 W/m²k

0.15 W/m²k

SuperQuilt, Standard Breather Membrane and 140mm PIR (0.022 W/mk)

0.14 W/m²k

0.13 W/m²k

SuperQuilt, Standard Breather Membrane and SuperQuilt

0.19 W/m²k

0.18 W/m²k

Fixing Instructions


A spider clip is fitted on to the wall tie against the inner leaf and this creates the minimum cavity between the product and the blockwork. The initial run of SuperQuilt is positioned over the wall ties, ensuring that it is kept taut but with sufficient drop to below floor insulation. SuperQuilt can be cut with a sharp blade to fit onto wall ties. The top edge of the material should be a minimum of 75mm over the top row of the wall ties giving a weathered lap joint.

When a full run is in position, the retaining clip is fixed to the wall tie to keep the SuperQuilt central to the cavity.

The second leaf is built up to the topmost line of the wall ties, (or two courses below) and the second run of SuperQuilt installed ensuring a minimum lap of 75mm. Vertical joints in the SuperQuilt should always be on a line of wall ties, ensuring a 100mm lap (ie 50mm either side of the wall tie) and sealed using ThermaSeal Foil Tape.

At internal and external corners a recommended air space of 25mm must be maintained.

U-Value Combined Method (W/m ² K)			0.24
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.040
Brick, External	102.50	0.770	0.133
Cavity	50.00	-	0.740
SuperQuilt	7.00	-	1.52
Cavity	20.00	-	0.740
Thermal Block	100.00	0.110	0.909
Plaster Dabs	15.00	-	0.170
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.130



U-Value table

Description

	100mm Cavity	110mm Cavity
SuperQuilt and 100mm Dense Block (1.130 W/mk)	0.31 W/m ² k	0.29 W/m ² k
SuperQuilt and 100mm Medium Block (0.500 W/mk)	0.30 W/m ² k	0.28 W/m ² k
SuperQuilt and 100mm Lightweight Block (0.250 W/mk)	0.29 W/m ² k	0.27 W/m ² k
SuperQuilt and 100mm Thermal Block (1.110 W/mk)	0.26 W/m ² k	0.24 W/m ² k
SuperQuilt and 100mm Thermal Block (0.110 W/mk) Thin Mortar	0.25 W/m ² k	0.24 W/m ² k
SuperQuilt and 140mm Dense Block (1.130 W/mk)	0.31 W/m ² k	0.29 W/m ² k
SuperQuilt and 140mm Medium Block (0.500 W/mk)	0.29 W/m ² k	0.27 W/m ² k
SuperQuilt and 140mm Lightweight Block (0.250 W/mk)	0.25 W/m ² k	0.26 W/m ² k
SuperQuilt and 140mm Thermal Block (1.110 W/mk)	0.24 W/m ² k	0.23 W/m ² k
SuperQuilt and 140mm Thermal Block (0.110 W/mk) Thin Mortar	0.23 W/m ² k	0.22 W/m ² k

Fixing Instructions

Vertical counter battens, minimum 25mm by 38mm battens are fixed to the wall at 400mm centres. Battens must always be placed at the top and bottom of the wall and around the perimeter of doors and windows.

SuperQuilt is applied directly from the roll either vertically or horizontally depending on the wall height, pulled tight and stapled onto the battens at minimum 300mm centres.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the battens, the joins should be sealed using **ThermaSeal Foil Tape**

Counter battens are fixed to the wall battens through the material at 600mm centres.


The plasterboard is fixed over the SuperQuilt and onto the battens in the usual manner.

If there is a concern regarding condensation because of the installation of an insulating vapour barrier, please supply full build up information on fax or email to our technical team and they can carry out a condensation risk analysis for you.

Watch our How-To Video For SuperQuilt on Walls by scanning the QR Code Here!



U-Value Combined Method (W/m ² K)			0.28
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.040
Brick, External	100.00	0.770	0.292
Cavity	50.00	-	0.180
Block	100.00	1.130	0.89
Batten Cavity	38.00	-	0.740
SuperQuilt	7.00	-	1.52
Batten Cavity	38.00	-	0.740
Insulated Plasterboard	30.00	-	0.560
Inside Surface	-	-	0.130



U-Value table

Description

SuperQuilt and Solid Wall

25mm Batten

0.34 W/m²k

38mm Batten

0.29 W/m²k

SuperQuilt, Solid Wall and 30mm Insulated Plasterboard EPS

0.29 W/m²k

0.26 W/m²k

SuperQuilt, Solid Wall and 40mm Insulated Plasterboard EPS

0.27 W/m²k

0.24 W/m²k

SuperQuilt, Solid Wall and SuperQuilt

0.22 W/m²k

0.19 W/m²k

SuperQuilt and Cavity Wall un-insulated

0.33 W/m²k

0.28 W/m²k

SuperQuilt, Cavity Wall un-insulated & 30mm Ins. Plasterboard EPS

0.28 W/m²k

0.25 W/m²k

SuperQuilt, Cavity Wall un-insulated & 40mm Ins. Plasterboard EPS

0.26 W/m²k

0.23 W/m²k

SuperQuilt, Cavity Wall un-insulated & SuperQuilt

0.22 W/m²k

0.18 W/m²k

SuperQuilt and Cavity Wall Insulated

0.25 W/m²k

0.22 W/m²k

SuperQuilt, Cavity Wall Insulated & 30mm Ins. Plasterboard EPS

0.23 W/m²k

0.21 W/m²k

SuperQuilt, Cavity Wall Insulated & 40mm Ins. Plasterboard EPS

0.22 W/m²k

0.20 W/m²k

SuperQuilt, Cavity Wall Insulated & SuperQuilt

0.18 W/m²k

0.16 W/m²k

Fixing Instructions

Installation of SuperQuilt for dwarf wall applications with additional insulation products should be in accordance with the certificate, YBS fixing instructions and current good building practice.


SuperQuilt is applied directly from the roll either vertically or horizontally depending on the wall height, pulled tight and stapled onto the timber studs at minimum 300mm centres.

SuperQuilt should be overlapped at each joint by approx. 50mm and stapled onto the battens, the joins should be sealed using **ThermaSeal Foil Tape**. Perpendicular counter battens, recommended 25mm by 38mm are fixed to the wall. Battens must always be placed at the top and bottom of the wall and around the perimeter of doors and windows. The plasterboard is fixed over the products and onto the battens in the usual manner.

Watch our How-To Video For SuperQuilt on Walls by scanning the QR Code Here!



U-Value Combined Method (W/m²K)			0.19
	Thickness (mm)	Conductivity (W/mK)	Resistance (m²K/W)
Outside Surface	-	-	0.040
Loft Void	-	-	0.500
PIR (Between Studs)	50.00	0.22	2.174
Stud cavity	35.00		0.740
SuperQuilt	7.00	-	1.52
Batten Cavity	38.00		0.740
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.130



U-Value table

Description

SuperQuilt and 50mm Glasswool (0.040 W/mk)
 SuperQuilt and 100mm Glasswool (0.040 W/mk)
 SuperQuilt and 25mm PIR (0.022 W/mk)
 SuperQuilt and 50mm PIR (0.022 W/mk)
 SuperQuilt and 75mm PIR (0.022 W/mk)
 SuperQuilt and 100mm PIR (0.022 W/mk)
 SuperQuilt Two Layer

25mm Batten

0.24 W/m²k
 0.19 W/m²k
 0.25 W/m²k
 0.21 W/m²k
 0.18 W/m²k
 0.16 W/m²k
 0.21 W/m²k

38mm Batten

0.22 W/m²k
 0.18 W/m²k
 0.23 W/m²k
 0.19 W/m²k
 0.17 W/m²k
 0.15 W/m²k
 0.19 W/m²k

Fixing Instructions

All timber exposed to the outer cavity, except naturally durable species should be treated.

SuperQuilt is applied directly from the roll either vertically or horizontally depending on the wall height, pulled tight and stapled onto the timber battens at minimum 300 mm centres.


SuperQuilt should be overlapped at each joint by approximately 50 mm and stapled onto the battens, the joints should be sealed **ThermaSeal Foil Tape**.

Vertical battens, recommended 25 mm by 38 mm are fixed to the vertical battens; battens should always be placed at the top and bottom of the wall and around the perimeter of doors and windows. The carrier board is fixed over the product and onto the battens, the external rendered finishing should comply with BS EN 13914-119.

Watch our How-To Video For SuperQuilt on Walls by scanning the QR Code Here!



U-Value Combined Method (W/m ² K)			0.30
	Thickness (mm)	Conductivity (W/mK)	Resistance (m ² K/W)
Outside Surface	-	-	0.390
Render	19.00	-	-
Render Board	22.00	-	-
Batten (Ventilated Cavity)	38.00	-	-
SuperQuilt	7.00	-	1.52
Batten Cavity	38.00	-	0.740
Brickwork	225.00	0.560	0.402
Drylining - plaster dabs	15.00	-	0.170
Plasterboard	12.50	0.190	0.066
Inside Surface	-	-	0.130



U-Value table

Solid Wall

SuperQuilt and Cladding
SuperQuilt and Render Board (Ventilated Cavity)

Cavity Wall

SuperQuilt and Cladding
SuperQuilt and Render Board (Ventilated Cavity)

25mm Batten

0.30 W/m²k
0.33 W/m²k

25mm Batten

0.30 W/m²k
0.33 W/m²k

38mm Batten

0.26 W/m²k
0.30 W/m²k

38mm Batten

0.27 W/m²k
0.31 W/m²k

HOW DOES SUPERQUILT WORK?

Due to the special composition of multi-layers of insulation, SuperQuilt effectively deals with all forms of energy transfer (i.e. conduction, convection and radiation). SuperQuilt works most effectively by reflecting infra-red radiation. This means that not only is SuperQuilt effective in winter by reflecting heat back into the building and cold out, but also in summer, SuperQuilt is a very effective barrier to solar overheating which reduces the need for artificial cooling systems as it prevents the accumulation of heat within the building.

GENERAL FIXING INSTRUCTIONS

Installation of SuperQuilt for floor applications should be in accordance with the certificate, YBS fixing instructions and current good building practice.

SuperQuilt must be installed with a 50mm overlap. SuperQuilt can be cut with a YBS SuperQuilt cutter, craft knife or a sharp pair of scissors.

SuperQuilt can be easily fixed with staples at regular intervals. Minimum 14mm stainless steel or galvanised staples are recommended.

No protective clothing/handling required.

Benefits

- **Fast and simple installation**
- **High core thermal resistance of 4.45m²K/W**
- **Tear Resistant**
- **Effective in summer and winter**
- **For suspended & floating floors**
- **Lightweight, thin & flexible**

P/A Ratio

The heat loss in a floor is greater at the exposed perimeter edge of the floor. To calculate the U-value, the exposed perimeter edge to area ratio needs to be worked out e.g. a 100m² area, semi-detached house with 3 external walls of 10m each has a perimeter to area ratio 0.3 (i.e. 30m :100m² = 0.3).




Fixing Instructions

SuperQuilt is rolled out over the joists, then stapled in place to create required airspace or nailed in place through the YBS saddle clips to maintain the required 50mm airspace

(4 saddle clips per m²). The horizontal joints are tightly overlapped and left open to allow any moisture accumulation to dissipate. SuperQuilt should be sealed around the perimeter or brought up above the floor deck. The decking is then fixed at 200mm centres with screws 37mm into the joists.

SuperQuilt can be used in conjunction with Superfloor Clips to provide a channel for underfloor heating pipework; please visit www.ybsinsulation.com and look under Superfloor for more information. (Please note that thermal outputs for underfloor heating have not been tested with SuperQuilt)




U-Value table

P/A Ratio	U-Value (with 50mm Cavity above)	U-Value (with 100mm Cavity above)
0.1	0.13 W/m ² k	0.12 W/m ² k
0.2	0.18 W/m ² k	0.16 W/m ² k
0.3	0.21 W/m ² k	0.18 W/m ² k
0.4	0.22 W/m ² k	0.20 W/m ² k
0.5	0.24 W/m ² k	0.20 W/m ² k
0.6	0.24 W/m ² k	0.21 W/m ² k
0.7	0.25 W/m ² k	0.22 W/m ² k
0.8	0.26 W/m ² k	0.22 W/m ² k
0.9	0.26 W/m ² k	0.23 W/m ² k
1	0.27 W/m ² k	0.23 W/m ² k

Fixing Instructions

SuperQuilt is rolled out onto the concrete floor leaving enough edge overlap to protrude above the floor deck. Timber joists/battens are then laid on top of the SuperQuilt, spaced at centres to suit the particular flooring. The deck is then fixed at 200mm centres with screws 37mm into the joists/battens.



U-Value table

P/A Ratio	U-Value (with 50mm Cavity above)	U-Value (with 100mm Cavity above)
0.1	0.13 W/m ² k	0.12 W/m ² k
0.2	0.20 W/m ² k	0.17 W/m ² k
0.3	0.24 W/m ² k	0.20 W/m ² k
0.4	0.26 W/m ² k	0.22 W/m ² k
0.5	0.28 W/m ² k	0.23 W/m ² k
0.6	0.30 W/m ² k	0.24 W/m ² k
0.7	0.31 W/m ² k	0.25 W/m ² k
0.8	0.32 W/m ² k	0.26 W/m ² k
0.9	0.33 W/m ² k	0.27 W/m ² k
1	0.34 W/m ² k	0.27 W/m ² k

Fixing Instructions

SuperQuilt is rolled out under the floor joists than stapled in place. Access is gained using the under floor crawl space. The horizontal joints are tightly overlapped and left open to allow any moisture accumulation to dissipate. SuperQuilt should be sealed around the perimeter or brought up above the floor deck.


Accessories



EcoPro Multifoil Fitting Kit



ThermoSeal Foil Tape



Construction	Thickness (mm)
Inside Surface	-
Tongue & Groove Floorboards	22.00
Joist Cavity	150.00
SuperQuilt	7.00
Ventilated Void	-
Ground	-

U-Value table

P/A Ratio	U-Value (with 150mm Cavity above)	U-Value (with 200mm Cavity above)
0.1	0.11 W/m ² k	0.11 W/m ² k
0.2	0.14 W/m ² k	0.14 W/m ² k
0.3	0.16 W/m ² k	0.15 W/m ² k
0.4	0.17 W/m ² k	0.16 W/m ² k
0.5	0.18 W/m ² k	0.17 W/m ² k
0.6	0.18 W/m ² k	0.17 W/m ² k
0.7	0.19 W/m ² k	0.18 W/m ² k
0.8	0.19 W/m ² k	0.18 W/m ² k
0.9	0.19 W/m ² k	0.18 W/m ² k
1	0.20 W/m ² k	0.19 W/m ² k



**Try Our Free & Easy To Use Online U-Value Calculator!
1,000s Of Calculations For Roofs, Walls & Floors.**



SuperQuilt

Tel : 0114 323 00 45

www.superquilt-insulation.co.uk

Technical@SuperQuilt-Insulation.co.uk

